## All-in-one 2 Mega-pixel Pan/tilt IP Network Camera



## Plug&Play H.264 wireless IP cameras View on iPhone/iPad and Android

The IP Camera is designed for all day video surveillance on your iPhone/iPad and Android mobiles/pads. The setup is truly 1-2-3:

- 1. Connect the camera to the network
- 2. Download the app mCamView into your iPhone/iPad or Android
- 3. View video by the camera ID/password

The push notification is supported, so that you will get the notification from your iPhone/iPad and Android once there is any events detected through the PIR body sensor or sound detector on the camera, even when your mobile is on sleep mode.

The pan/tilt functions allow the mobile user to pan./tilt the camera through a

finger move on the mobile screen. You could monitor the whole room with a single camera.

The SD card recording is supported, and you could playback the recorded video on your iPhone/iPad and Android. You could also do the SD card recording only when there is PIR or sound detection to save the SD card storage size. The PIR and sound detected recording has a 5 seconds pre-recording, so that you will always catch the critical moment.

The NAS storage is supported. You can record the video files into any normal NAS devices or to your Dropbox account. And you can playback those recorded video files remotely on your mobile devices or computers.

For day & night usage, there are two video sensors/lens on the camera, one for day and one for night. The day lens and night lens focus are separately tuned for day light and Infra Red light for best video quality. No ICR, no mechanical problem.

Two-way audio is supported. You can monitor the synchronized video/audio and talk to or warn the people around the camera from your iPhone/iPad and Android once you got the push notification. There is a built-in speaker and a speaker jack is provided so that you could connect any high power speaker to the camera for your needs.

The WPS(WiFi Protected Setup) is supported. You could set up the WiFi connection of the camera with the router by clicking the WPS button on the camera and on the router at the same time. No more complicated WiFi configuration.

The IP camera is ideal for securing small businesses, home offices and residences. The IP Camera is a perfect replacement of the alarm system and baby monitor in your house and shop. .

## **Features**

- ➤ Plug & play by ID/password, no IP address or DNS settings.
- ➤ H.264 video compression
- ➤ 2 Mega-pixel for up to 1920x1080 resolution at 30 fps.
- > Pan/tilt control.
- Two sensors/lens for day and night separately.
- PIR body detection, effective distance 7 meters.

- > Two way audio.
- ➤ SD card video recording with 5 seconds of pre-recording..
- ➤ 802.11 n wireless with WEP and WPA/WPA2 security support.
- WPS (WiFi Protected Setup) support.
- > Triple video streaming on PC, mobile and SD card recording.
- ➤ Night mode control support automatic, manual and scheduled modes.
- ➤ Connect up to 8 users simultaneously
- > Bundle with free video management software CamView.
- Push notification on iPhone/iPad and Android for PIR and sound detection.
- Email/ftp alarm message for PIR and sound detection.
- > Event scheduling.
- ➤ Video recording on NAS device.
- Cloud Storage on Dropbox.
- ➤ Internal real time clock
- ➤ Watchdog function to prevent system failure.

## **Specifications**

**Models** 2 Mega-pixel with Pan/tilt

Power DC 12V, 1A

**Processors** RISC CPU, hardware video processing and compression.

**Network interface** Ethernet 10BaseT/100BaseTX, Auto-MDIX, RJ-45

**Wireless interface** 2.4G Hz WiFi

Range: 100 meters, line of sight

**Pan/Tilt control** Pan viewing range  $180^{\circ}$  (  $-90^{\circ} \sim 90^{\circ}$  )

Tilt viewing range  $90^{\circ}$  (  $0^{\circ} \sim 90^{\circ}$  )

Image sensor RGB 2 Mega 1/4 inch CMOS

Day and night separate sensors

Automatic exposure control, automatic white balance, automatic gain control, automatic brightness control.

**PIR sensor** Effective distance – 7 meters

**Light sensitivity** 0.2 Lux (IR LED off)

0 Lux (with 10 meters IR LED on)

Automatically turn on the IR LED on low light

environment.

Lens 3.3 mm, F2.8, viewing angle: 70°, fixed iris.

focus range: 50 cm to infinity Day and night separate lens

**Buttons** One reset button, to factory default settings

One WPS button for automatic WiFi setup

**Indicators** One LED for Internet connection status indication

One LED for Ethernet connection indication
One LED for SD card recording indication

**Video compression** H.264, high profile

Video streaming Separate frame rate/resolution/bandwidth settings

for PC and mobile.

**Video settings** Resolution: 1920x1080, 1280x720, 640x360

Bandwidth: 64k, 128k, 256k, 512k, 768k, 1M, 1.2M, 1.5M, 2M, 3M

bps

Frame rate :  $1\sim5$ , 10, 15, 20, 25, 30 fps

**Audio** Built-in microphone for audio monitoring

Built-in 0.5W speaker for alarm and half-duplex two-way

audio.

Speaker jack for external speaker

Audio compression: G.711

**Security** Web management username/password protection

Video display ID/password protection

WiFi WEP and WPA/WPA2 security mode

**Installation,** Plug & play by ID/password.

management and Video management software-CamView for video access

maintenance and multi-camera management

Firmware upgrades via FTP

Web browsing Built-in web server for standard web browser access

Video snapshot on any browser

**Supported protocols** IPv4, HTTP, TCP, ICMP, RTSP, RTP, UDP, RTCP,

SMTP, SNTP, FTP, DHCP, ARP, DNS, PPPoE, etc.

Accessories (included) Power adaptor, RJ45 Ethernet cable, quick installation

guide, CD with installation software and User's Manual,

ID/Password card.

**Video management** Surveillance software for viewing and archiving up to 36

software cameras

App MCamView2 for Android and iPhone

Users Up to 8 simultaneous unicast users

(depends on video settings)

**Alarm and event** Events triggered by PIR and sound detection

management Email/ftp alarm message

Push notification on iPhone/iPad and Android devices.

**Dimensions (HxWxD)** 124 x 91 x 100 mm,

and weight 350 g, camera body only

**Operating conditions** 0-50 °C

Humidity 20 – 80% RH (non-condensing)