Waterproof Varifocal 5MP IP Camera



PoE waterproof IP cameras View on iPhone/iPad and Android

The IP Camera is designed for all day/night video surveillance on your iPhone/iPad and Android mobiles/pads and Windows software.

The setup is truly 1-2-3:

- 1. Connect the camera to the network
- 2. Download the app mCamView into your iPhone/iPad or Android
- 3. View video by the camera ID/password

The camera is using a motorized varifocal lens for remote viewing of different distance, the viewing angle is from 110° to 32° by controlling the varifocal lens of focal length from 2.7mm to 13.5mm on the mobile App or Window software. The IR LEDs will adjust automatically for different viewing angle to achieve the maximum distance of up to 50 meters.

The PoE(Power over Ethernet) is supported for the most stable network

connection.

The camera is for waterproof/outdoor usage, with the IP67 rated housing, the camera is totally dust and rain proof and suitable for operation under poor weather condition.

For day & night usage, there are IR LEDs and IR cut on the camera, IR filter is on for day and off for night usage.

The push notification is supported, so that you will get the notification from your iPhone/iPad and Android once there is any events detected through the motion detection or sound detection on the camera, even when your mobile is on sleep mode.

The SD card recording is supported, and you could playback the recorded video on your iPhone/iPad and Android. You could also do the SD card recording only when there is motion or sound detection to save the SD card storage size. The motion and sound detected recording has a 5 seconds pre-recording, so that you will always catch the critical moment.

The Time Lapse Recording is supported. The camera can do time lapse recording on the SD card and you can playback the recorded time lapse video on the mobile or tablet remotely, anywhere. This is more convenient than traditional time lapse camera which can only be played back by removing the SD card to a computer.

The ONVIF protocol is supported. You could record the video to standard NVR device. The supported ONVIF profiles are Profile S,T,G,Q.

The NAS and cloud storage is supported. You can record the video files into any normal NAS devices or to your Dropbox account. And you can playback those recorded video files remotely on your mobile devices or computers.

The IP camera is ideal for securing small businesses, home offices and residences. The IP Camera is a perfect replacement of the alarm system and traditional analog CCTV camera in your house and shop.

Features

- > 5 mega-pixel video resolution 2592x1944 for 30 fps
- ➤ Motorized varifocal lens of focal length 2.7~13.5mm.

- ➤ Plug & play by ID/password, no IP address or DNS settings.
- ➤ PoE (Power over Ethernet) supported.
- > IP67 rated housing
- ➤ H.264/H.265 video compression
- ➤ Support ONVIF Profile S,T,G,Q
- > Day and night video with high power IR led.
- > SD card video recording with 5 seconds of pre-recording..
- > Time lapse video recording
- > Triple video streaming on PC, mobile and SD card recording.
- ➤ Night mode control support automatic, manual and scheduled modes.
- Connect up to 8 users simultaneously
- ➤ Bundle with free video management software CamView(Windows)/mCamView2(iOS/Android).
- ➤ Push notification on iPhone/iPad and Android for motion and sound detection.
- Email/ftp alarm message for motion and sound detection.
- > Event scheduling.
- ➤ Video recording on NAS device.
- Cloud storage on Dropbox.
- ➤ Internal real time clock
- ➤ Watchdog function to prevent system failure.

Specifications

Models Varifocal 5MP IP Camera

Power PoE or DC 12V, 1A

Processors RISC CPU, hardware video processing and compression.

Network interface PoE (Power over Ethernet) supported

Housing IP67 rated water proof

Image sensorRGB 5 Mega 1/2.7 inch CMOS sensor

Automatic exposure control, automatic white balance, automatic gain control, automatic brightness control.

Light sensitivity 0.2 Lux (IR LED off)

0 Lux (with 10~50 meters IR LED on)

Automatically turn on the IR LED on low light

environment.

IR LED 4 high power IR LEDs.

Lens M12, 2.7~13.5 mm, F1.4,

viewing angle- horizontal:32°~110°,

Fixed iris. focal range: 50 cm to infinity

Buttons One reset button, to factory default settings

Indicators One LED for Internet connection status indication

One LED for Ethernet connection indication
One LED for SD card recording indication

Video compression H.264/H.265, high profile

Video streaming Separate frame rate/resolution/bandwidth settings

for PC and mobile.

Video settings Resolution: (5 mega) 2592x1944, (4 mega)2688x1520,

(FHD)1920x1080, 1280x720, 640x360

Bandwidth: 64k, 128k, 256k, 512k, 768k, 1M, 1.2M, 1.5M, 2M, 3M

bps

Frame rate: 1~5, 10, 15, 20, 25, 30 fps

Audio Built-in microphone for audio monitoring

Audio compression: G.711

Security Web management username/password protection

Video display ID/password protection

Installation, Plug & play by ID/password.

management and Video management software-CamView for video access

maintenance and multi-camera management

Firmware upgrades via FTP/SFTP?HTTP

Web browsing Built-in web server for standard web browser access

Video snapshot on any browser

Supported protocols IPv4, HTTP, TCP, ICMP, RTSP, RTP, UDP, RTCP,

SMTP, SNTP, FTP, SFTP, DHCP, ARP, DNS, PPPoE,

etc.

Accessories (included) RJ45 Ethernet cable, quick installation guide,

ID/Password card.

Video management Surveillance software for viewing and archiving up to 36

software cameras

Users Up to 8 simultaneous unicast users

(depends on video settings)

Alarm and event Events triggered by motion and sound detection

management Email/ftp alarm message

Push notification on iPhone/iPad and Android devices.

Dimensions (HxWxD) 90 x 120 x 120 mm.

Weight 470 g.

Operating temperature Starting Temperature: $-20^{\circ}\text{C} \sim 50^{\circ}\text{C} (-4^{\circ}\text{F} \sim 122^{\circ}\text{F})$

Working Temperature: $-30^{\circ}\text{C} \sim 50^{\circ}\text{C} (-22^{\circ}\text{F} \sim 122^{\circ}\text{F})$